



Gray cast iron is the most versatile of all foundry metals. Its high carbon percentage makes foundry fusion and manufacturing of machinery easier. This grade of iron has a high resistance and it obtains its maximum hardness as a result of a refined control of the chemical composition, size, and type of the graphite flake. D-LINE® cast iron valves are designed under MSS-SP, ASME, ANSI standards to meet the quality required by the market.

APPLICATIONS

D-LINE® Gate Valves serve multi-national end users in a wide range of applications in many industries including:



- Water Treatment
- Food industries
- Waste treatment
- Oil & Gas industries
- Steam services

DESIGN FEATURES

- Outside screw and yoke
- Face to face to per ANSI B16.10
- Flange dimensions to per ASME B16.1
- Shell wall thickness to per ASME B16.34
- Valve design to per MSS SP-70
- Bronze seat
- Solid wedge
- Steam service working pressure: 125 PSI
- WOG service working pressure: 200 PSI

TEST SPECIFICATION	
TEST ACCORDANCE TO PER API 598	
CLASS	125
NOMINAL PRESSURE	200 PSI
SHELL TEST (WATER)	350 PSI
SEAT TEST (WATER)	200 PSI
AIR TEST	87 PSI


FEATURES	
SIZE	2" - 12"
CLASS	125
CONNECTION	FF
TEMPERATURE	-29°C TO 232°C

MARKING BODY	
FRONT	BACK
CL.B	
3	
	
125	

PRESSURE - TEMPERATURE RATING


These are conservative guide for general service.

Previous experience in process or new development may permit applications above those shown.



Cast Iron ASTM A-126 Gr. B
MSS SP-70 Ratings
Material Limits

DIMENSIONS



VALVE MATERIAL LIST		
No.	DESCRIPTION	MATERIAL
1	BODY	ASTM A-126 Gr. B
2	BODY RING	ASTM B62
3	WEDGE RING	ASTM B62
4	GASKET	ASTM A-126 Gr. B
5	STEM	ASTM A-276 Gr. 420
6	NUT	ASTM A-536 Gr. A
7	BOLTS	ASTM A-307 Gr. B
8	GASKET	GRAPHITE
9	BONNET	ASTM A-126 Gr. B
10	PACKING	GRAPHITE
11	BOLTS	ASTM B16
12	NUT	ASTM B16
13	GLAND	ASTM A-536 Gr. 65-45-12
14	STEM NUT	ASTM B16
15	BONNET LOCK NUT	ASTM A-126 Gr. B
16	SCREW	ASTM A-307 Gr. B
17	HANDWHEEL	ASTM A-126 Gr. B
18	HANDWHEEL NUTS	ASTM A-536 Gr. 65-45-12

VALVE DIMENSIONS & WEIGHTS

MODEL	SIZE		PORT	A	B	C	D	E	F	Gmin	Gmax	WEIGHT (KG)
144BR-09	2"	DN50	2.00	7.00	6.00	4.75	0.63	4.00	0.75	12.17	14.45	14.61
144BR-10	2 1/2"	DN65	2.50	7.50	7.00	5.50	0.69	4.00	0.75	13.46	16.42	18.00
144BR-11	3"	DN80	3.00	8.00	7.50	6.00	0.75	4.00	0.75	14.96	18.31	25.03
144BR-12	4"	DN100	4.00	9.00	9.00	7.50	0.94	8.00	0.75	16.44	20.77	36.20
144BR-13	5"	DN125	5.00	10.00	10.00	8.50	0.94	8.00	0.87	19.11	24.40	43.20
144BR-14	6"	DN150	6.00	10.50	11.00	9.50	1.00	8.00	0.87	22.07	28.35	62.10
144BR-15	8"	DN200	8.00	11.50	13.50	11.75	1.12	8.00	0.87	28.17	36.62	101.00
144BR-16	10"	DN250	10.00	13.00	16.00	14.25	1.19	12.00	1.00	33.07	43.84	159.00
144BR-17	12"	DN300	12.00	14.00	19.00	17.00	1.25	12.00	1.00	39.50	51.85	231.00

*WEIGHT IS ESTIMATED

*ALL DIMENSIONS ARE EXPRESSED IN INCHES



< Scan the QR CODE to see our available studs.